

## SERVICE SPECIFICATIONS

### TORQUE SPECIFICATIONS

Part tightened	N·m	kgf·cm	ft·lbf
<b>HOOD</b>			
Hood support X Hood	22	225	16
Hood support X Body	22	225	16
<b>TRANSPORT HOOK</b>			
Front Transport Hook			
Front transport hook X Body	64	650	47
Rear Transport Hook			
Rear transport hook X Body	64	650	47
<b>SEAT</b>			
Front seat			
Power seat regulator X Body	37	375	27
Seat back assembly X Seat cushion assembly	26	260	19
Power seat regulator X Seat cushion assembly	26	260	19
Rear seat			
Rear seat back X Body	18	185	13
<b>SEAT BELT</b>			
Front Seat Belt			
Front seat outer belt anchor X Body	43	440	32
Front seat outer belt lower side X Body	43	440	32
ELR X Body	43	440	32
Front seat inner belt X Power seat regulator	43	440	32
Rear Seat Belt			
Rear seat outer belt anchor X Body	43	440	32
ELR X Body	43	440	32
Rear seat inner belt X Body	43	440	32
<b>BUMPER</b>			
Front Bumper			
Front bumper reinforcement X Body	13	130	9.4
Rear Bumper			
Rear bumper reinforcement X Body	13	130	9.4

## Specifications (Fitting Adjustments)

