

GENERAL DESCRIPTION

1. Care must be taken to replace each part properly as it could affect the performance of the brake system and result in a driving hazard. Replace the parts with parts of the same part number or equivalent.
2. It is very important to keep parts and the area clean when repairing the brake system.


DESCRIPTION

The service brakes consist of a foot brake which changes rotational energy to thermal energy to stop the vehicle while it is being driven and a parking brake to keep the vehicle from moving while it is parked.

OPERATION

FOOT BRAKE


When the brake pedal is depressed, a vacuum builds up in the booster which amplifies the pedal force, pressing on the piston in the master cylinder. The piston raises the hydraulic pressure in the cylinder. This hydraulic pressure is then applied to each respective brake cylinder, and acts to press the brake pads against the rotating rotor discs. The resulting friction converts the rotational energy to thermal energy, stopping the vehicle.



R00002

PARKING BRAKE

When the parking brake lever is pulled up, the parking brake shoe lever is pulled via the parking brake wire. This causes the shoe strut to push the front shoe, which expands and is pressed against the rotor disc. If the parking brake lever continues to be pulled up, the contact point of the parking brake shoe lever and shoe strut then becomes the fulcrum so that the parking brake shoe lever causes the rear shoe to expand. This results in the rotor disc being locked by the front shoe and rear shoe.



BR5361R