

SERVICE SPECIFICATIONS

ENGINE

Drive belt tension			A drive belt tensioner is used, so check that the drive belt tension is not necessary.		
Engine coolant capacity (w/ Heater)			10.8 liter	11.4 US qts	9.5 Imp. qts
Engine oil capacity (Drain and refill)	w/ Oil filter change		4.8 liter	5.1 US qts	4.2 Imp. qts
	w/o Oil filter change		4.5 liter	4.8 US qts	4.0 Imp. qts
Spark plug	Type	ND	PK20R11		
		NGK	BKR6EP11		
	Gap		1.1 mm	0.043 in.	
Firing order			1 – 8 – 4 – 3 – 6 – 5 – 7 – 2		
Valve clearance (Cold)	Intake		0.15–0.25 mm	0.006–0.010 in.	
	Exhaust		0.25–0.35 mm	0.010–0.014 in.	

CHASSIS

Front and rear brake				
Pad thickness	Limit		1.0 mm	0.039 in.
Disc thickness	Limit	Front	30.0 mm	1.181 in.
		Rear	15.0 mm	0.591 in.
Disc runout	Limit		0.05 mm	0.0020 in.
Parking brake				
Lining thickness	Limit		1.0 mm	0.039 in.
Drum inside diameter	Limit		191.0 mm	7.52 in.
Front axle and suspension				
Lower ball joint vertical play			0.3 mm	0.012 in.
Steering wheel play			30 mm (1.18 in.) or less	
Torque specifications				
Front seat mounting bolts			37 N·m	375 kgf·cm 27 ft·lbf
Front suspension crossmember X	Nut (Front side)		127 N·m	1,300 kgf·cm 94 ft·lbf
Body	Bolt (Rear side)		201 N·m	2,050 kgf·cm 148 ft·lbf
Rear suspension member X Body	Front side		176 N·m	1,800 kgf·cm 130 ft·lbf
	Rear side		38 N·m	390 kgf·cm 28 ft·lbf