

TORQUE SPECIFICATION

Part tightened		N·m	kgf·cm	ft·lbf
Engine block x Transmission	14 mm head	37	380	27
	17 mm head	72	730	53
Starter x Transmission		37	380	27
Rear support member x Body		25	260	19
Rear support member x Transmission mounting bracket		13	130	9
Transmission mounting bracket x Extension housing		25	250	18
Extension housing x Transmission case		34	345	25
Valve body x Transmission case		10	100	7
Oil strainer		10	100	7
Oil pan		7.3	75	65 in·lbf
O/D direct clutch speed sensor		5.4	55	48 in·lbf
Vehicle speed sensor		5.4	55	48 in·lbf
ATF Temp. sensor wiring clamp set bolt		6.6	68	58 in·lbf
Solenoid wiring clamp set bolt		10	100	7
Park/neutral position switch	Bolt	13	130	9
	Nut	3.9	40	35 in·lbf
Control shift lever x Park/neutral position switch		16	160	12
Drain plug		20	205	15
Solenoid valve x Valve body		10	100	7
Parking lock pawl bracket		7.4	75	65 in·lbf
Rear center floor crossmember brace x Body		13	130	9
Heat insulator x Body		5.4	55	48 in·lbf
Transmission control rod x Shift lever sub-assembly		13	130	9
Oil cooler clamp set bolt		5.4	55	48 in·lbf
Oil cooler pipe union nut		44	450	33
Drive plate x Crankshaft		83	850	61
Torque converter clutch x Drive plate		48	490	35