

# BODY

## TORQUE SPECIFICATION

SS0H3-01

| Part tightened                                     | N·m | kgf·cm | ft·lbf     |
|--|-----|--------|------------|
| FRONT BUMPER                                       | –   | –      | –          |
| Front bumper reinforcement x Body                  | 13  | 130    | 9          |
| REAR BUMPER  | –   | –      | –          |
| Rear bumper reinforcement x Body                   | 13  | 130    | 9          |
| HOOD   | –   | –      | –          |
| Hood auxiliary catch hook x Hood                   | 8.3 | 85     | 75 in.·lbf |
| Hood support x Hood                                | 22  | 225    | 16         |
| Hood support x Body                                | 22  | 225    | 16         |
| Hood hinge x Hood                                  | 13  | 130    | 9          |
| FRONT DOOR   | –   | –      | –          |
| Door lock x Door panel                             | 5.4 | 55     | 48 in.·lbf |
| Window regulator x Door panel                      | 5.4 | 55     | 48 in.·lbf |
| LUGGAGE COMPARTMENT                                | –   | –      | –          |
| Lock striker x Door                                | 5.4 | 55     | 48 in.·lbf |
| Door hinge x Door                                  | 8.3 | 85     | 74 in.·lbf |
| Door support x Door Hinge                          | 22  | 225    | 16         |
| Door lock x Body                                   | 5.4 | 55     | 48 in.·lbf |
| INSTRUMENT PANEL                                   | –   | –      | –          |
| Instrument panel x Front passenger airbag assembly | 13  | 133    | 10         |
| SEAT   | –   | –      | –          |
| Front Seat   | –   | –      | –          |
| Front seat x Body                                  | 37  | 375    | 27         |
| Seatback assembly x Seat cushion assembly          | 26  | 260    | 19         |
| Power seat regulator x Seatback assembly           | 26  | 260    | 19         |
| Front seat link with front vertical                | 11  | 110    | 8.0        |
| Front seat link with rear vertical                 | 11  | 110    | 8.0        |
| Rear Seat  | –   | –      | –          |
| Rear seatback x Body                               | 18  | 185    | 13         |
| SEAT BELT  | –   | –      | –          |
| Front Seat Belt                                    | –   | –      | –          |
| Front seat outer belt anchor x Body                | 42  | 430    | 31         |
| Sill bar x Body                                    | 42  | 430    | 31         |
| ELR x Body (Upper side)                            | 7.5 | 76     | 55 in.·lbf |
| ELR x Body (Lower side)                            | 42  | 430    | 31         |
| Front seat inner belt x Body                       | 42  | 430    | 31         |
| Rear Seat Belt                                     | –   | –      | –          |
| Rear seat outer belt anchor x Body                 | 42  | 430    | 31         |
| ELR x Body   | 42  | 430    | 31         |
| Rear seat inner belt x Body                        | 42  | 430    | 31         |
| CRS, Tether anchor                                 | 21  | 210    | 15         |
| Center belt x Body                                 | 42  | 430    | 31         |