

TORQUE SPECIFICATION

Part tightened	N·m	kgf·cm	ft·lbf
Master cylinder x Piston stopper bolts	10	100	7
Master cylinder x Reservoir	1.7	17.5	15.2 in.·lbf
Master cylinder x Brake booster	13	130	9
Brake line union nut	15	155	11
Brake booster clevis lock nut	25	260	19
Brake booster x Pedal bracket	12	125	9
Bleeder plug	11	110	8
Front brake torque plate x Steering knuckle	118	1,200	87
Front brake caliper installation bolt	34	350	25
Front brake caliper x Flexible hose union bolt	30	310	22
Rear brake torque plate x Axle carrier	104	1,065	77
Rear brake caliper installation bolt	34	350	25
Rear brake caliper x Flexible hose union bolt	30	310	22
Parking brake lever x Floor	59	600	43
Parking brake cable No.1 x Floor	9	80	69 in.·lbf
Parking brake cable retainer x Floor	5.4	55	48 in.·lbf
Parking brake cable clamp x Floor	17	190	14
ABS (& TRAC) actuator x Actuator bracket	5.4	55	48 in.·lbf
ABS (& TRAC) actuator bracket x Body	19	195	14
ABS & TRAC actuator bleeder plug	8.3	85	74 in.·lbf
Front speed sensor installation bolt	7.8	80	69 in.·lbf
Rear speed sensor installation bolt	7.8	80	69 in.·lbf
Speed sensor harness clamp bolt and nut	5.4	55	48 in.·lbf