

TORQUE SPECIFICATION

Part tightened		N·m	kgf·cm	ft·lbf
Transmission x Engine	12 mm bolt	72	730	53
	10 mm bolt	37	380	27
Engine rear mounting x Transmission		25	250	18
Rear engine mounting member	Nut	13	135	10
	Bolt	25	260	19
Starter x Transmission		39	400	29
Clutch release cylinder x Clutch housing		12	120	9
Flexible hose bracket set bolt		37	380	27
Transmission shift lever x Transmission		19	195	14
Crossmember brace x Body		13	130	9
Heat insulator x Body		5.4	55	48 in.·lbf
Exhaust center pipe x Tail pipe		19	195	14
Exhaust front pipe x Exhaust center pipe		43	440	32
Exhaust pipe support bracket set bolt		37	380	27
Exhaust No.2 front pipe x Exhaust front pipe		43	440	32
Oxygen sensor set nut		18	180	13
Shift lever x Control shift lever arm		7.8	80	69 in.·lbf
Shift fork set bolt		20	200	14
Straight screw plug		25	250	18
Reverse idler gear shaft stopper bolt		25	250	18
Oil separator x Intermediate plate		18	185	13
Front bearing retainer set bolt		25	250	18
Extension housing x Intermediate plate		37	380	27
Restrict pin		40	410	30
Shift lever housing x Shift and select lever shaft		39	400	29
Control shift lever retainer x Extension housing		18	185	13
No.2 inner shift lever x Control shaft		36	365	26
No.1 control shift yoke x Control shaft		19	195	14
Drain and filler plugs		37	380	27
Back-up light switch		40	410	30
Vehicle speed sensor set bolt		13	130	9
Control shift lever arm x Control shift lever retainer		25	250	18
Control shift lever arm x Extension housing		19	195	14
Clutch housing x Transmission case		37	380	27
Rear bearing retainer x Intermediate plate		18	185	13