

## TORQUE SPECIFICATION

Part tightened	N·m	kgf·cm	ft·lbf
Union bolt	15	150	11
Fuel line for flare nut	31	310	23
Fuel pump bracket x Fuel tank	5.4	55	48 in.·lbf
Fuel pump set plate x Fuel tank	3.9	40	35 in.·lbf
Fuel tank x Body	25	250	18
Fuel inlet pipe x Fuel tank	2.9	30	26 in.·lbf
Fuel sender gauge x Fuel tank	2.9	30	26 in.·lbf
Fuel return tube x Fuel tank	29	300	22
Fuel pressure regulator x Delivery pipe	29	300	22
Throttle body x Air intake chamber	18	185	13
Delivery pipe x Intake manifold	18	185	13
Fuel inlet hose x LH delivery pipe for SST	39	400	29
	33	340	24
IAC valve x Air intake chamber	18	185	13
VSV for fuel pressure control x Air intake chamber	18	185	13
ECT sensor x Front water bypass joint	25	250	18
EGR gas temperature sensor x EGR valve adaptor	20	200	14
EGR valve adapter x Air intake chamber	19	195	14
Knock sensor x Cylinder block	44	450	33
Heated oxygen sensor (sensor1) x Exhaust manifold	44	450	33
Heated oxygen sensor (sensor2) x Front exhaust pipe	44	450	33